



AGMAR /9 server rack in configuration A as standard is available in 16 sizes and two colors - RAL7035 and RAL9005. Perfect for small systems. Light side walls made of aluminum significantly facilitate their installation. A wide range of accessories allows to configure a complete enclosure.

SUPPLY INCLUDES:

Frame: made of powder-coated steel, welded structure with system holes

Front door: one-piece, perforated 85%, 4-point locking system, handle with patent lock, 180° hinges

Rear door: vertically divided 50/50, perforated 85%, 4-point locking system, handle with patent lock, 180° hinges

Side walls: light, made of aluminum, divided horizontally, tool-free assembly

Roof: flat roof with two side cable entry in the depth, prepared for fan mounting plate

Rack 19": 2 pairs of 19" type B profile, marking of the height of individual U

Grounding: copper busbar with a set of grounding cables

Server racks | Configuration A | usable height 24U and 42U

Dimensions								
Usable height [U]	24		24		24		42	
Width [mm]	600		800		800		600	
Depth [mm]	800		800		1000		800	
Total height [mm]	1165		1165		1165		1965	
Total width [mm]	600		800		800		600	
Total depth [mm]	850		850		1050		850	
Color	RAL7035	RAL9005	RAL7035	RAL9005	RAL7035	RAL9005	RAL7035	RAL9005
Max load [kg]	1500	1500	1500	1500	1500	1500	1500	1500
Distance between refitted 19" [mm]	520	520	520	520	720	720	520	520
Calatog number	7130-24681	7130-24682	7130-24881	7130-24882	7130-24801	7130-24802	7130-42681	7130-42682

Server racks | Configuration A | usable height 42U

Dimensions								
Usable height [U]	42		42		42		42	
Width [mm]	600		600		800		800	
Depth [mm]	1000		1200		800		1000	
Total height [mm]	1965		1965		1965		1965	
Total width [mm]	600		600		800		800	
Total depth [mm]	1050		1250		850		1050	
Color	RAL7035	RAL9005	RAL7035	RAL9005	RAL7035	RAL9005	RAL7035	RAL9005
Max load [kg]	1500	1500	1500	1500	1500	1500	1500	1500
Distance between refitted 19" [mm]	720	720	720	720	520	520	720	720
Calatog number	7130-42601	7130-42602	7130-42621	7130-42622	7130-42881	7130-42882	7130-42801	7130-42802

Server racks | Configuration A | usable height 42U and 47U

Dimensions								
Usable height [U]	42		47		47		47	
Width [mm]	800		600		600		600	
Depth [mm]	1200		800		1000		1200	
Total height [mm]	1965		2188		2188		2188	
Total width [mm]	800		600		600		600	
Total depth [mm]	1250		850		1050		1250	
Color	RAL7035	RAL9005	RAL7035	RAL9005	RAL7035	RAL9005	RAL7035	RAL9005
Max load [kg]	1500	1500	1500	1500	1500	1500	1500	1500
Distance between refitted 19" [mm]	720	720	520	520	720	720	720	720
Calatog number	7130-42821	7130-42822	7130-47681	7130-47682	7130-47601	7130-47602	7130-47621	7130-47622

Server racks | Configuration A | usable height 47U | width 800

Dimensions								
Usable height [U]	47		47		47		47	
Width [mm]	800		800		800		800	
Depth [mm]	800		1000		1200		1200	
Total height [mm]	2188		2188		2188		2188	
Total width [mm]	800		800		800		800	
Total depth [mm]	850		1050		1250		1250	
Color	RAL7035	RAL9005	RAL7035	RAL9005	RAL7035	RAL9005	RAL7035	RAL9005
Max load [kg]	1500	1500	1500	1500	1500	1500	1500	1500
Distance between refitted 19" [mm]	520	520	720	720	720	720	720	720
Calatog number	7130-47881	7130-47882	7130-47801	7130-47802	7130-47821	7130-47822	7130-47821	7130-47822